Pickering - PXI Switching Map

PXI PXIe The **PXI/PXIe** icon denotes that modules are available in both **PXI** and **PXIe** formats. Pickering is committed to making many more of its **PXI** products available as **PXIe**.

GENERAL PURPOSE SWITCHES

	Low Density (<50 Relays)			High Density						Medium Power (2 A to 5 A)										Switched Guard
Features	• Low Cost General Purpose • Uses High Reliability Pickering Reed Relays			• Highest Density PXI Modules • Pin Compatible With 40-145/6/8 • PXI/PXIe Versions for 40-140B			• Pin Compatible With 40-140B/141/143 • 60 W Maximum Power			• Medium Power Relays	• Low Cost Relay Module For Medium Power Switching Applications			• Power Ruthenium Reed Relays		• High Density • Highly Versatile Mixed Relay Configurations	• High Density	• High Density Power Relays		• Very High Density Electro-Mechanical Relay Module	• Up to 10^{12} Ω Isolation Resistance
Model Family	40-110	40-115		40-140B	40-141	40-143	40-145A	40-146A	40-148A	40-130	40-131	40-132		40-136		40-138	40-139A	40-137		40-100	40-121
Configurations	16 or 32 x SPDT	16 or 32 x SPST	16 or 24 x DPST	50, 75 or 100 x SPST	50 x DPST	48 or 64 x SPDT	50, 75 or 100 x SPST (NO or NC)	25 or 50 x DPST	32, 48 or 64 x SPDT	8 or 13 x DPDT	16 or 26 x SPDT	16 or 32 x SPST	16 or 19 x DPST	16, 25 or 32 x SPST	12, 16 or 19 x DPST	Module accepts mix of SPST, DPST, SPDT & DPDT Relays	Up to 80 x SPST, 40 x DPST, 52 x SPDT or 26 x DPDT	16 x SPST	32 or 39 x SPST	83 x SPDT	13 or 26 x SPST
Relay Type	Pickering Instrumentation Reed			Pickering Instrumentation Reed			Electro-mechanical			Electro-mechanical				Pickering Reed		Electro-mechanical		Electro-mechanical		Electro-mechanical	Ruthenium Reed
Max Switch Voltage	150 VDC/100 VAC			150 VDC/100 VAC						220 VDC/125 VAC	300 VDC/250 VAC			200 V		300 VDC/250 VAC		110 VDC/250 VAC		200 VDC/140 VAC	100 V
Max Switch/Carry Current	0.25 A/1 A	1 A/1.2 A		1 A		0.25 A/1 A	1 A			2 A				1 A/2.5 A or 1 A/2 A		2 A		5 A	2 A	2 A	1 A
Max Switch Power	3 W	20 W		20 W		3 W	60 W			60 W				40 W		60 W		150 W	90 W	60 W	20 W
Typical Operate Time	0.5 ms			0.5 ms			3 ms			3 ms				0.5 ms		3 ms		10 ms		3 ms	0.5 ms
Connector Type	96-pin Micro-D			200-pin LFH						50 or 78-pin D-type				50 or 78-pin D-type		160-pin DIN 41612		37-pin D-type	78-pin D-type	500-pin SEARAY	26-Pin MS-M RF
Width (PXI-1, PXI-hybrid)	1-Slot			1-Slot						1-Slot										1-Slot	1-Slot

HIGH POWER SWITCHES

	High Power (5 A to 40 A)														
Features	• High Power • DPST and SPDT options		• PXI/PXIe Versions for 40/42-153/158		• High Power • SPST and DPST options		• High Density • High Current	• High Density • High Current	• Very High Power • Suitable For Automotive Test			• 50 A Peak	• 120 A Peak	• 90 A Peak	• 20 A Peak
Model Family	40-150/151	40-153	40-155/156/157	40-158	40-160		40-161A	40-166	40-170	40-180	40-181	40-182A	40-183B	40-184A	40-185A
Configurations	8 or 12 x DPST	Up to 50 x SPST	8 or 16 x SPDT, or 8 x DPDT	Up to 32 x SPDT	10 or 20 x SPST	10 x DPST	10, 12, 16 x SPST or 6, 12 x SPDT Inc. Optional Hardware Interlock	5 or 10 x SPST, 3 or 6 x SPDT or 1, 2 or 3 x SP4T	2 x SPST or 2 x DPST	2 or 4 x SPST	2 x SPDT	3 or 6 x SPST	6 x SPST	3 or 6 x SPST	
Relay Type	Electro-mechanical											Solid State			
Max Switch Voltage	125 VDC/250 VAC	110 VDC/250 VAC	300 VDC/250 VAC		125 VDC/250 VAC		300 VDC/ 250 VAC	300 VDC/480 VAC	30 VDC/ 250 VAC	14 VDC or 28 VDC		200 VDC/AC peak	40 VDC/AC peak	100 VDC/AC peak	400 VDC/AC peak
Max Switch/Carry Current	5 A				10 A	8 A	16 A	20 A, 30 A(SPST)	30 A or 20 A	40 A or 20 A		10 A	40 A	25 A	1.5 A
Max Switch Power	175 W/1250 VA	150 W/1250 VA	175 W/1250 VA		300 W/2500 VA	240 W/2000 VA	448 W/4000 VA	600 W/5500 VA	900 W/7500 VA, 600 W/5000 VA	560 W		2000 W	1600 W	2500 W	600 W
Typical Operate Time	10 ms		8 ms	10 ms	10 ms			22 ms	30 ms	15 ms		20 µs	250 µs		20 µs
Connector Type	37 or 50-pin D-type	37 or 50-pin D-type, or SGMC	37 or 50-pin D-type	37 or 50-pin D-type, or SGMC	20-pin GMCT			20-Pin Scorpion	8-pin Power D-type						
Width (PXI-1, PXI-hybrid)	1-Slot							1-Slot	2-Slot			1 or 2-Slot	2-Slot	1 or 2-Slot	

LOW, MEDIUM & HIGH DENSITY MATRICES

	Low Density (<128 Crosspoints)			Medium Density (128 to 256 Crosspoints)													
Features	• Reed Relay Matrix	• 2 A • 2-Pole	• Wide Current Range from 10 µA	• 2 A Matrix With up to 224 Crosspoints					BIRST	• Reed Relay Matrix				• Signal Insertion & Monitor Matrix	• 2 A Matrix • 128 Crosspoints BIRST		
Model Family	40-510/511/512/513	40-515/516/517	40-514	40-505	40-506	40-507	40-508	40-509	40-518A/519B	40-520	40-521	40-522	40-523/524	40-525A	40-527A	40-528B	40-529B
Configurations	1 or 2-Pole or 1-Pole Shielded: Single 12x4, 12x8, 24x4 or Dual 12x4	2-Pole: Single 8x8, 16x4 or Dual 8x4,	2-Pole: Single 6x4, X&Y Loop-thru; Single 6x8, Y Loop-thru.	1-Pole: Single 42x4	1-Pole: Single 32x6	1-Pole: Single 25x8	1-Pole: Single 18x12	1-Pole: Single 14x16	2-Pole: Single 16x8 or 32x4	1-Pole: Between 16x16 & 32x2	1 or 2-Pole: Single 24x8	1 or 2-Pole Dual 12x8	1-Pole, 2-Pole, 1-Pole Shielded: Single 44x4, or 1-Pole: 46x4	1 Pole: 16x4 or 34x4 with Switched Loop-Thru	1 Pole: Single 64x2	1 Pole: Single 32x4	1 Pole: Single 16x8
Relay Type	Pickering Instrumentation Reed	Electro-mechanical		Electro-mechanical						Pickering Instrumentation Reed				Electro-mechanical			
Max Switch Voltage	150 VDC/100 VAC	300 VDC/250 VAC	220 VDC/250 VAC	300 VDC/250 VAC						150 VDC/100 VAC				220 VDC/ 150 VAC	300 VDC/250 VAC		
Max Switch/Carry Current	1 A/1.2 A	2 A		2 A						1 A/1.2 A	0.5 A/1 A	1 A/ 1.25 A		2 A			
Max Switch Power	20 W	60 W	62.5 VA, 60 W	60 W						15 W	10 W	20 W		60 W			
Typical Operate Time	0.5 ms	3 ms	4 ms	6.5 ms					3 ms	0.5 ms				3 ms			
Connector Type	68-pin Micro-D	50-pin D-type		160-pin DIN41612	78-pin D-type	78-pin D-type	50-pin D-type	50-pin D-type	78-pin D-type	50-pin D-type	96-pin Micro-D			78-pin D-type		50-pin D-type	37-pin D-type
Width (PXI-1, PXI-hybrid)	1-Slot			1-Slot													

	High Density (256 to 528 Crosspoints)										
Features	• Fast Operate Time • Long Service Life		• Ultra High Density	BIRST	• Ultra High Density				• Highest Density in 1-Slot • 528 Crosspoints		
Model Family	40-500	40-501	40-530	40-533B	40-531/532	40-534A	40-538	40-535/536/537	40-540A	40-541A	40-542A
Configurations	1 Pole: Single 64x4		1 Pole: Single 32x8	1 or 2 Pole: Single 64x2 or 64x4	1 or 2-Pole or 1-Pole Shielded: Single 32x8 or Dual 16x8	1 or 2-Pole or 1-Pole Shielded: Dual 32x4	1-Pole: Single 55x8	1-Pole: Single 92x4, Single 44x8 or Dual 44x4	1-Pole: Single 132x4	1-Pole: Single 66x8	1-Pole: Single 33x16
Relay Type	Solid State		Pickering Instrumentation Reed								
Max Switch Voltage	±60 VDC/AC peak	±100 VDC/AC peak	150 VDC/100 VAC								
Max Switch/Carry Current	0.5 A	0.15 A	1 A		0.5 A						
Max Switch Power	30 W	15 W	20 W	15 W	10 W						
Typical Operate Time	400 µs		0.5 ms								
Connector Type	78-pin D-type		96-pin Micro-D	200-pin LFH	96-pin Micro-D	200-pin LFH	96-pin Micro-D		200-pin LFH	96-pin micro-D	68-pin micro-D
Width (PXI-1, PXI-hybrid)	1-Slot										

	High Density (256 to 528 Crosspoints)														Switched Guard	
Features	• Highest Density Single Slot 3U 2 A Matrices • Up to 448 Crosspoints					BIRST	• Ultra High Density	BIRST		• Highest Density 1-Slot 2 A Matrices BIRST				• Up to 70 MHz	• Up to 10^{12} Ω Isolation Resistance	Features
Model Family	40-575	40-576	40-577	40-578	40-579	40-580	40-581	40-582A	40-583	40-584A	40-585A	40-586B	40-587B	40-588	40-590	Model Family
Configurations	1-Pole: Single 84x4	1-Pole: Single 64x6	1-Pole: Single 50x8	1-Pole: Single 36x12	1-Pole: Single 28x16	2-Pole: Single 32x8	2-Pole: Single 33x8	2-Pole: Single 16x16	2-Pole: Single 64x4	1-Pole: Single 128x2	1-Pole: Single 64x4	1-Pole: Single 32x8	1-Pole: Single 16x16	2-Pole: 16x8 and 32x8	8x4 and 16x4	Configurations
Relay Type	Electro-mechanical														Ruthenium Reed	Relay Type
Max Switch Voltage	300 VDC/250 VAC					150 VDC/ 100 VAC		270 VDC/225 VAC	300 VDC/250 VAC					220 VDC/250 VAC	100 V	Max Switch Voltage
Max Switch/Carry Current	2 A						1 A	2 A						2 A	250 mA	Max Switch/Carry Current
Max Switch Power	60 W													62.5 VA, 60 W	10 W	Max Switch Power
Typical Operate Time	6.5 ms					3 ms								0.6 ms	0.5 ms	Typical Operate Time
Connector Type	160-pin DIN 41612	78-pin D-type	78-pin D-type	50-pin D-type	50-pin D-type	160-pin DIN 41612	96-pin micro-D	78-pin D-type	160-pin DIN 41612		78-pin D-type	50-pin D-type	37-pin D-type	104-pin D-Type	MMCX Coaxial	Connector Type
Width (PXI-1, PXI-hybrid)	1-Slot													2-Slot	1-Slot	Width (PXI-1, PXI-hybrid)

HIGH POWER MATRICES

	High Power (2 A to 40 A)							
Features	• High Density • 2 A	• High Density • 5 A	• 2-Pole • 5 A	• High Density • 10 A	• High Density • 16 A	• High Speed, Long Service Life • High Inrush Current		
Model Family	40-545/546/547/548	40-549	40-550	40-551	40-552	40-553A	40-554B	40-555B
Configurations	1-Pole: Single 10x4, 10x8, 20x4 or Dual 10x4	1-Pole: Single 8x4, 8x8, 16x4 or Dual 8x4	2-Pole: Single 8x4	1-Pole: Single 4x4, 8x2 or 8x4 (8x4 loop-thru option)	1-Pole: Single 4x4 or 8x2 with loop-thru option	1-Pole: Single 6x2		1-Pole: Single 8x2
Relay Type	Electro-mechanical					Solid State		
Max Switch Voltage	110 VDC/250 VAC		125 VDC/250 VAC		300 VDC/250 VAC	±200 VDC/AC peak	±40 VDC/AC peak	
Max Switch/Carry Current	2 A	5 A		10 A	16 A	10 A	40 A	
Max Switch Power	90 W/500 VA	150 W/1250 VA		300 W/2500 VA	448 W/4000 VA	2000 W	1600 W	
Typical Operate Time	10 ms	10 ms				120 µs	250 µs	
Connector Type	37-pin D-type	25-pin D-type	37-pin D or 20-pin GMCT	20-pin GMCT		8-pin Power D-type		
Width (PXI-1, PXI-hybrid)	1-Slot					2-Slot		

BRIC LARGE MATRICES

	High Density Matrix																					
Features	BIRST • New Generation of 0.5 A Matrices • Robust 0.5 A/5 W Switching With up to 9216 Crosspoints per Module				BIRST • New Generation of 1 A Matrices • Robust 1 A/20 W Switching With up to 4096 Crosspoints per Module					BIRST • Integrated PXI Matrix With Built In High Performance Analog Bus • Highest Quality Reed Relays					• Available as 2, 4, 8 or 12 Slot 3U Modules • x4, x8, x16 & x32 Options • Built-In Self Test							
Model Family	40-558				40-559					40-560B			40-561A		40-562B				40-563A			
Configurations	1-Pole: From 168x6 to 1512x6	1-Pole: From 128x8 to 1152x8	1-Pole: From 84x12 to 756x12	1-Pole: From 64x16 to 576x16	1-Pole: From 256x4 to 1024x4	1-Pole: From 168x6 to 672x6	1-Pole: From 128x8 to 512x8	1-Pole: From 84x12 to 336x12	1-Pole: From 64x16 to 256x16	1-Pole: From 184x4 to 1656x4	1-Pole: From 92x8 to 828x8	1-Pole: From 46x16 to 414x16	1 or 2-Pole: From 60x8 to 360x8	1 or 2-Pole: From 30x16 to 180x16	1 or 2-Pole: From 88x4 to 792x4	1 or 2-Pole: From 44x8 to 396x8	1 or 2-Pole: From 22x16 to 198x16	1-Pole: From 10x32 to 90x32	1-Pole: From 64x8 to 360x8			
Relay Type	Pickering Instrumentation Reed																		Solid State			
Max Switch Voltage	150 VDC/100 VAC				190 VDC/200 VAC					Up to 140 VDC/100 VAC			85 VDC/100 VAC		150 VDC/100 VAC				±40 V			
Max Switch/Carry Current	0.5 A				1 A/1.2 A					0.5 A					1 A/1.2 A				0.25 A			
Max Switch Power	5 W				20 W					10 W					20 W				10 W			
Typical Operate Time	1 ms																		20 µs			
Connector Type	100-pin Micro-D		68-pin Micro-D		160-pin DIN 41612	104-pin D-type	78-pin D-type		50-pin D-type	96-pin Micro-D	68-pin Micro-D		68 & 96-pin Micro-D	68-pin Micro-D	96-pin Micro-D	68-pin Micro-D						
Width (PXI-1, PXI-hybrid)	2, 4, 8 or 12-Slot				2, 4 or 8-Slot					2, 4, 8 or 12-Slot												

	2 A Matrix							
Features	• High Density 2-Pole Matrix • 60 W Switching • Built-In Self Test BIRST		• Very High Density 1-Pole Matrix • x4, x6, x8, x12 & x16 Options • Electro-mechanical Relays		• 60 W Switching • Available as 2, 4 or 8 Slot 3U PXI Modules			• ATE Switching System • Multiple Configurations • Designed For ARINC 608A Testing
Model Family	40-573	40-566B	40-568	40-596A	40-567A	40-597	40-598	40-569B
Configurations	2-Pole: From 29x8 to 232x8	2-Pole: From 55x4 to 385x4	1-Pole: From 75x4 to 600x4	1-Pole: From 58x6 to 464x6	1-Pole: From 44x8 to 352x8	1-Pole: From 32x12 to 256x12	1-Pole: From 24x16 to 192x16	1 or 2 Resource Distributor Cards (2-Pole: 8x4 & 16x4 Matrices) & up to 6 Bus Matrix Inputs Cards (Dual 4-Pole 16x2 Matrix)
Relay Type	Electro-mechanical							
Max Switch Voltage	240 VDC/250 VAC	300 VDC/250 VAC	200 VDC/140 VAC	300 VDC/250 VAC	100 VDC/70 VAC			200 VDC/180 VAC
Max Switch/Carry Current	2 A							
Max Switch Power	60 W							
Typical Operate Time	3 ms		6.5 ms					3 ms
Connector Type	78-pin D-type	160-pin DIN 41612 & 25-pin D-type	78-pin D-type		50-pin D-type	37-pin D-type	25-pin D-type	160-pin DIN 41612 & 50-pin D-type
Width (PXI-1, PXI-hybrid)	2, 4 or 8-Slot	4 or 8-Slot	2, 4 or 8-Slot					4 or 8-Slot

LOW DENSITY MULTIPLEXERS

	Low Density					Switched Guard
Features	• Low Density, Low Cost • Single and Dual Configurations		• Differential Thermal Offset <1.5 µV	• Low Cost • 2 A Switching	• Wide Current Range from 10 µA	• Up to 10^{12} Ω Isolation Resistance
Model Family	40-630A	40-632A	40-620A	40-635A	40-514	40-121
Configurations	1-Pole: Single 64:1 or Dual 32:1, 2-Pole: Single 32:1, Dual 16:1 or 4-Pole: Single 16:1	1-Pole: Single 48:1 Dual 24:1 2-Pole: Single 24:1	2-Pole: Single 23:1 Low Thermal EMF MUX	Between 1-Pole: Single 64:1 & 2-Pole: 4-Bank 8:1	1-Pole: Single 24:1, Dual 12:1, Quad 6:1. 2-Pole: Single 12:1, Dual 6:1, Quad 3:1. 4-Pole: Single 6:1 Dual 3:1.	8 or 16 2:1 Multiplexers
Relay Type	Pickering Instrumentation Reed			Electro-mechanical		Ruthenium Reed
Max Switch Voltage	150 VDC/100 VAC		100 V	300 VDC/250 VAC	220 VDC/250 VAC	100 V
Max Switch/Carry Current	1 A/1.2 A		0.5 A/1 A	2 A	2 A/2.5:A	1 A
Max Switch Power	20 W			60 W	62.5 VA, 60 W	20 W
Typical Operate Time	0.5 ms			3 ms	4 ms	0.5 ms
Connector Type	68-pin Micro-D		96-pin Micro-D	78-pin D-type	37 & 50-pin D-type	26-Pin MS-M RF
Width (PXI-1, PXI-hybrid)	1-Slot					1-Slot

HIGH DENSITY MULTIPLEXERS

	High Density																				
Features	• Very High Density • Wide Range of Configurations		• Multiple Configurations • High Speed, Long Life	• Configurable • Equivalent to 40-612A			• Configurable with Inter-bank Relays		• High Density	• Wide Range of Configurations	• High Density • Low Cost • PXI/PXIe (40/42-675B)		• Versatile - Many Possible Configurations • Software Configurable		• Low Cost • Wide Range of Configurations	• Configurable • 2-Pole Switching	• High Density • 2-Pole Switching	• High Density • 2-Pole Switching	• High Density MUX in Pickering BRIC format	• MUX + SPST Switches • Designed for ARINC 608A Testing	• MUX with DMM Monitor Function
Model Family	40-610A	40-615A	40-680	40-681A	40-682A	40-683A	40-616A	40-617A	40-640A	40-670C	40-675B	40-611A	40-612B	40-613A	40-614D	40-655A	40-656A	40-659A	40-570A	40-618A	40-619
Configurations	Between 1-Pole: Single 128:1 & 2-Pole: 8-Bank 8:1, (1-Pole shielded reed available)	Between 1-Pole: Single 160:1 & 2-Pole: 20-Bank 4:1	1-Pole: Between Single 160:1 & 20-Bank 8:1	Between 1-Pole: Single 128:1 & 2-Pole: 8-Bank 8:1			1-Pole: 16-Bank 5:1	1-Pole: 18-Bank 3:1	Single 1-Pole: 94:1 or 2-Pole: 47:1	Between 1-Pole: Single 198:1 & 32-Pole Single 5:1	Between 1-Pole: Single 198:1 & 32-Pole: Single 5:1	1-Pole: Single 158:1 or 2-Pole: Single 79:1	8 Basic Configurations from 1-Pole: Single 128:1 to 2-Pole: 8-Bank 8:1	5 Basic 2-Pole Configurations from: Single 64:1 to 16-Bank 4:1	22 Configurations, 1 to 32 Poles, 1 to 16 Banks, 4 to 128 Channels,	2-Pole: 7-Bank 4:1	2-Pole: Single 38:1	2-Pole: 8-Bank 8:1	Max configurations between 160-Pole: 6:1 & 10-Pole: 96:1 with switched loop-thru	Source Switch (12-Bank 4:1 MUX & 44 x SPST Switches)	9 Configurations: 1-Pole: Single, Dual and Quad Versions, 16, 25, 32, 64 or 128 Channels
Relay Type	Pickering Instrumentation Reed		Solid State				Pickering Instrumentation Reed				Electro-mechanical										
Max Switch Voltage	150 VDC/100 VAC		±15 V	±60 V	±40 V	±100 V	100 V		150 VDC/100 VAC			300 VDC/250 VAC				220 VDC/125 VAC		300 VDC/250 VAC	100 VDC/100 VAC peak	300 VDC/250 VAC	250 VAC/DC
Max Switch/Carry Current	1 A/1.2 A		20 mA	350 mA	250 mA	125 mA	1 A		0.5 A/1.2 A	0.5 A	1 A	2 A						2 A	1 A	2 A	2 A
Max Switch Power	20 W		3 W	21 W	10 W	12.5 W	20 W			10 W	60 W									60 W	60 W (62.5 VA)
Typical Operate Time	0.5 ms		200 ns	200 µs	80 µs	500 µs	0.5 ms				3 ms			6 ms	3 ms	4.5 ms		3 ms		3 ms	6 ms
Connector Type	200-pin LFH			160-pin DIN 41612			96-pin Micro-D			200-pin LFH		160-pin DIN 41612				78-pin D-type		160-pin DIN 41612		160-pin DIN 41612	160-pin DIN 41612
Width (PXI-1, PXI-hybrid)	1-Slot																		8-Slot	1-Slot	1-Slot

HIGH POWER MULTIPLEXERS

	High Power													
Features	• 5 A Power MUX	• 5 A MUX - Multiple Configurations	• High Speed • Long Life	• High Density • 1-Pole Switching	• Power & Sense MUX	• Power MUX in Pickering BRIC format	• 1 or 2-Pole Power MUX • 10 A or 8 A Current Handling			• High Density • 10 A Switching • 1-Pole	• High Density • 16 A Switching • 1-Pole	• Suitable For Automotive Test	• High Speed, Long Life • High Inrush Current	
Model Family	40-650A	40-651A	40-652A	40-657A	40-658A	40-571A	40-660A		40-665A	40-661A	40-662A	40-664A	40-666B	40-667C
Configurations	2-Pole: Single 16:1	1-Pole: 1-Bank 48:1, 2-Bank 24:1, 4-Bank 11:1 or 8-Bank 5:1	1-Pole: Single 24:1 & 48:1, Dual 24:1, 2-Pole: Single 24:1	1-Pole: 8-Bank 8:1, 4-Bank 16:1, 2-Bank 32:1 or Single 64:1	2-Pole: Dual 18:1	Max configurations between 6-Pole: 48:1 & 48-Pole: 6:1 with loop-thru	2-Pole: Single 10:1	1-Pole: Single 10:1	1-Pole: Single 18:1	8-Bank 4:1, 5-Bank 6:1, 4-Bank 4:1 or 8:1, Dual 8:1 or 16:1, Single 16:1 or 32:1,	Quad 2:1, Quad 4:1, Dual 4:1, Dual 8:1, Single 8:1, Single 12:1 or Single 16:1	1-Pole: Single 4:1	1-Pole: Single 6:1 or Dual 3:1	
Relay Type	Electro-mechanical		Solid State	Electro-mechanical	Instrumentation Reed	Electro-mechanical							Solid State	
Max Switch Voltage	125 VDC/250 VAC	110 VDC/250 VAC	±100 V	110 VDC/250 VAC	200 VDC/240 VAC (Power) & 200 VDC (Sense)	100 VDC/100 VAC peak	125 VDC/250 VAC				300 VDC/250 VAC	14 VDC or 28 VDC	±200 VDC/ AC peak	±40 VDC/ AC peak
Max Switch/Carry Current	5 A			2 A	1 A/2 A (Power), 1 A/1.2 A (Sense)	3 A	8 A	10 A			16 A	20 A or 40 A	10 A	40 A
Max Switch Power	175 W/1250 VA	150 W/1250 VA	500 W	90 W/500 VA	40 W (Power), 20 W (Sense)	105 W	240 W/2000 VA	300 W/2500 VA			448 W/4000 VA	560 W	2000 W	1600 W
Typical Operate Time	10.5 ms		85 µs	10.5 ms	0.5 ms	10.5 ms	10.5 ms				8.5 ms	15.5 ms	120 µs	250 µs
Connector Type	37-pin D-type	9 & 50-pin D-type	50-pin D-type	78-pin D-type		50-pin D-type	20-pin GMCT					8-pin Power D-type		
Width (PXI-1, PXI-hybrid)	1-Slot					8-Slot	1-Slot					2-Slot		

pickering

pickeringtest.com

CHASSIS & REMOTE CONTROLLERS



	PXI Chassis				PXI Controllers	PXI/PXIe Hybrid Chassis			PXIe Controllers		LXI Ethernet/USB Chassis				
															
Chassis Slots	8-Slot	19-Slot	8-Slot	14-Slot	–	8-Slot	18-Slot	21-Slot	–	–	2-Slot	4-Slot	6-Slot	7-Slot	18-Slot
Features	• High Performance Chassis • Remote Management System	• High Performance Chassis • Remote Management System	• 6 Mechanical Expansion Slots for Efficient Housing of Wide Modules e.g. BRIC	• High Performance Chassis • Hot Swappable PSUs	• PCIe to PXI Control Interface Kit • Provides a PCI Express Interface	• Gen3 High Performance Chassis • Remote Management System	• Gen2 & Gen3 High Performance Chassis • Remote Management System	• Gen2 High Performance Chassis • 20 PXIe Hybrid Peripheral Slots • Very High Power and Cooling Capacity	• PXIe Embedded Controller • Max Throughput 14GB/s • Compact for Versatility	• PCIe to PXIe Control Interface Kit • Daisy Chain Option	• Compact chassis for hosting Pickering's 3U PXI modules in an LXI environment, allowing remote control over an Ethernet or USB connection				
Model Family	40-924	40-923A	40-908	40-914	41-924/51-924	42-924	42-925/42-926	42-927	43-920	43-921-001/002 and Kits	60-104	60-105	60-106	60-102D	60-103D

Choosing a Chassis for Pickering PXI Modules

(Please note the chassis slot width for all required modules when selecting a chassis)

CHASSIS SELECTION GUIDE:

PXI and PXIe (with PXIe and/or Hybrid Slots)

- Mix our 1000+ PXI Switching & Simulation modules with any vendors' PXI/PXIe instrumentation
- Embedded or remote Windows PC control
- Real-time operating system support
- High data bandwidths, especially with PXI Express
- Integrated module timing and synchronization

Pickering LXI or LXI/USB Modular Chassis (Only accept our PXI Switching & Simulation Modules):

- Choose from 1000+ Pickering PXI modules
- Ethernet or USB control enables remote operation
- Low-cost control from practically any controller
- LXI provides manual control via Web browsers
- Driverless software support
- Power sequencing immunity
- Ethernet provides chassis/controller voltage isolation
- Independence from Windows operating system

3U PXI modules are compatible with the following chassis types:

- All chassis conforming to the 3U PXI and 3U Compact PCI (cPCI) specification
- Legacy and hybrid peripheral slots in a 3U PXI Express (PXIe) chassis
- Pickering Interfaces LXI or LXI/USB modular chassis

3U PXIe versions of the modules are compatible with the following chassis types:

- All chassis conforming to the 3U PXIe specification
- PXIe and hybrid peripheral slots in a 3U PXI Express (PXIe) chassis

USB, COMMUNICATIONS & OPTICAL SWITCHING

	USB Switch	Telecoms/Differential Switching					Optical Switching			
Features	• Data Comms MUX For USB1 & USB2	• Tributary Switches • Suitable for Telecoms Test Applications		• Data Comms MUX For Switching USB and RS232	• Data Comms MUX For Switching AFDX, Ethernet, LVDS, USB and RS232	• Multiplexer Designed For Differential Signals • MIL-STD-1553	• MEMS Technology Offering High Reliability & Fast Operating Speed • Available With Single-Mode or Multi-Mode Support			
Model Family	40-737A	40-792/793	40-795/796	40-735	40-736	40-739	40-850A	40-852A	40-855A	40-860A
Configurations	4-Pole: Single 8 or 16-Channel	1-Pole (75Ω) 8 or 16-Channel Tributary Switch	2-Pole (100/120Ω) 8 or 16-Channel Tributary Switch	Single 36, Dual 18 or Single 18 Channel	8-Channel / 4-Pair, 16-Channel / 2-Pair & 32-Channel / 1-Pair	Single or Dual 4, 8 or 16-channel differential switching	Single 4-Channel MUX	Single 8-Channel MUX	Single, Dual, Triple or Quad 2-Channel MUX	Single, Dual, Triple, Quad Insert/Bypass Switch
Relay Type	Electro-mechanical	Electro-mechanical		Reed & Electro-mechanical	Electro-mechanical	Electro-mechanical	MEMS Optical			
Max Switch Voltage	100 V	100 VDC/100 VAC		150 VDC/100 VAC	100 V	–	–			
Max Switch/Carry Current	0.5 A data, 2 A power	1 A		0.5 A	0.3 A	0.8 A	–			
Max Switch Power	60 W	30 W		10 W	60 W	60 W	–			
Typical Operate Time	3 ms	10 ms		4 ms	3 ms	3 ms	1 ms			
Connector Type	USB or 78-pin D-type	96-pin Micro-D			78-pin D-type	78-pin D-type	FC/APC, FC/PC, SC/PC, MU (mini SC), LC, SC, ST			
Width (PXI-1, PXI-hybrid)	1-Slot	1-Slot					1 or 2-Slot			

RF SWITCHES & MULTIPLEXERS

| | RF SPDT Switch | | | | RF Multiplexer | | | | |